

ArcticChill 98

Direct Chill Cooler

The ArcticChill 98
Direct Chill Cooler
With Ambient
Water



23cm Dispensing
Height To Fill
Bottles

AA[®]FIRST
WATER COOLERS
& BOILERS



CE RoHS

refreshingly different

- Chiller capacity: 20 ltr of below 12C chilled water/hour
- Ambient capacity: virtually unlimited
- Can be fitted with drip tray overflow kits & mains drainage
- Fits our standard cowl and wall bracket
- FloodGuard inlet solenoid protects the cooler against large scale flooding
- Impressive 23cm dispensing height

ArcticChill 98

Direct Chill Cooler

Key Features



Eco Light Sensor Turns The Cooler Off Overnight To Save Approx 25% Pa In Electricity!



Select Ambient Or Cold, Then Hold The Dispensing Button Down

Accessories For The ArcticChill 98

Installation Rail With Filter. Includes Compression Fitting, 1-Micron Green Filter, Water Block, Copper Pressure Reducing Valve & Non-Return Valve.



FloodGuard - Closed Inlet Solenoid Only Opens To Allow Water Into The Cooler, When Water Is Dispensed. By Remaining Closed All Other Times It Protects The Cooler Against Leaks.



Filter Housing With Carbon Block Candle & Nanofilter.



Mains Drainage - Connect The Drip Tray To Mains Drainage. Can Be Supplied With A Pump, To Pump The Water Over 50m & A Rise Of 5m.



A Pumped Main Drainage System Pumps The Waste Water From The Drip Tray Over A Distance Of 100m & A Rise Of 5m. (Factory Installed).



3 Litre Overflow Kit Connects The Drip Tray To A 3 Litre Alarmed Overflow Container. The Container Has A Tap To Empty Without Removing It.



Cowling To Fix The Cooler Securely To The Wall (Supplied Separately).



10 Litre Overflow System With Alarm To Signal When Full (Factory Fitted).



Description	Hourly Output		Temp	Dimensions H x W x D mm	Weight (Kg)
	Chilled	Ambient			
POU Floor Standing	20 ltr	Indefinite	Below 12c	1135 x 340 x 340	25

Local Distributor



AAFIRST
WATER COOLERS
& BOILERS

www.aafirst.co.uk